








REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE



SEC A-A



RECOMMENDED PCB LAYOUT

Note:

1.Material:

- 1.1 Housing: High temperature thermoplastic with g.f,UL94v-0
- 1.2 Contact: copper alloy,t=0.15mm
- 1.3 Shell: copper alloy,t=0.25mm

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
- 2.3 Contact resistance: 30 MΩ Max.
- 2.4 Insulation resistance: 100 MΩ Min.
- 2.5 Total mating force: 3.57 Kgf Max.
- 2.6 Total unmating force: 1.0 Kgf Min.
- 2.7 Temperature range: -30°C~80°C

A 01 S B 1 4 1 B 3-379

- ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

- ① 产品代号 A:成品
- ② 产品系列 01:micro usb 5pin
- ③ 产品类别 S:母座
- ④ 产品类型 B:B TYPE
- ⑤ 外壳材质 1:G2680R-1/2H
- ⑥ 端子材质 4:G5191R-EH
- ⑦ 主体材质 1:LCP
- ⑧ 主体颜色 B:黑色
- ⑨ 下板类型 3:沉板式
- ⑩ 细节序号 379:Micro usb 5s B Type Smt沉板式0.8四脚全插有导位

PART NO: A01SB141B3-379		MATERIAL: SEE NOTE	
MODEL NO: XX		FINISH: SEE NOTE	
UNIT: MM	SIZE: A4	COLOR: SEE NOTE	TITLE: Micro usb 5s B Type Smt沉板式0.8四脚全插有导位
TOLERANCE UNSPECIFIED		DR: xiayouhong	DWG NO: A379
.x	0.15	CHK:	REV: A
.xx	0.10	APP:	SCALE: 5:1
.xxx	0.05		DATE: 2014.03.01
Ang	1°		